## COPPERHEAD PROFLEX® by **NCC**



#### **Automatic screen printing press**



M&R Global DCC 's Copperhead Pro Flex ™ presses are the benchmark in automatic screen printing presses, combining highest quality components, leading-class craftsmanship and high-speed production to create an outstanding press at an affordable price. An electric indexing system enables extremely smooth and quiet operation. The included, innovative squeegee pressure equalizer system with regulators on each printhead speeds setup and ensures uniform ink deposit for excellent print quality.

Electric printheads, tool-free squeegee/floodbar angle adjustment, pneumatic screen frame clamps and independent squeegee/flood speeds provide operators with all the time-saving features needed for quick setups.

### **FEATURES**

- Available In 10 Stations
- Standard Pallet Size: 38 x 56 cm (15" x 22")
- Maximum Image Area: 35 x 38 cm (14" x 15")
- Standard Front- and Rear-Locking Micro-Registration
- Standard Pneumatic Screen Frame Clamps
- High-Resolution Touchscreen Control Panel with Easy-to-Use, Icon-Based Logic and Built-In Tutorial Screens
- Print Stack Mode Enables HD and Other **Specialty Print Techniques**

Find more information and where to buy at: www.mrprintglobal.com




# COPPERHEAD PROFLEX by DCC

#### **Smooth Print Strokes • Quiet Operation • Tool-Free Adjustments**

Copperhead Pro flex features a squeegee equalizer system with individual regulators on each head ensures uniform ink deposit for excellent print quality.

With 10 station configurations, there is sure to be a Copperhead Pro flex that meets your needs.



Printhead controls are conveniently located for easy access and adjustment



Individual mechanical heads lift for quick screen cleaning

SPECIFICATIONS	PRO FLEX 10/8
Air @ 7 Bar (102 psi)	565 I/min (20 cfm)
Electrical Requirements <sup>1</sup>	380-415 V, 3 ph, 14.5 A, 50 Hz, 6.75 kW
Diameter	416 cm (164")
Maximum Frame Size	51 x 69 cm (22" x 27") OD
Standard Image Area	35 x 38 cm (14" x 15")
Machine Weight	1592 kg (3510 lb)
Standard Pallet Size	38 x 56 cm (15" x 22")
Stations/Colors	10/8
The mint with a second (IDO) to a few and making from the first stimulation of mint and a few and a second control of the second con	

<sup>1</sup>Use uninterruptible power supply (UPS) to safeguard machine from voltage fluctuation out of main supply.

If incoming voltage differs from the voltage(s) listed in the brochure, calculate amperage accordingly.

M&R Printing Equipment, Inc. • www.mrprint.com
440 Medinah Road, Roselle, Illinois 60172-2329 USA

DCC Group • www.mrprintglobal.com 802, Kamla Executive Park, JB Nagar, Andheri (E), Mumbai, 400059, India

USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • India: +91 98719-88775

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No varranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2024 M&R Printing Equipment, Inc. All rights resorted. 2025;0515