

MODEL T02-1300

Special calender for pieces or continuous fabrics, used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

1. CHARACTERISTICS OF PRINTING CYLINDER:

- 1.1. Diameter: 200 mm (7,87").
- 1.2. Width: 1.300 mm (51,1").
- 1.3. Working Width: 1.150 mm (45,2").

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. Temperature of the cylinder is set by the touch screen and regulated by an electronic card. The temperature controls equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

- 3.1. Tension control for printing material in roll:
 - Entry: brake with manual adjustment
 - Exit: winding with manual adjustment device
- 3.2. Tension control for printing paper in roll:
 - Entry: disk brake with manual adjustment
 - Exit: winding with manual adjustment device
- 3.3. Tension control for protection paper:
 - Entry: disk brake with manual adjustment
 - Exit: winding with manual adjustment device

4. OTHER DEVICES INTO MACHINE:

- 4.1. Short front working table, 800 mm
- 4.2. Single motor
- 4.3. NOMEX felt with manual tension adjustment system and automatic felt-centering device
- 4.4. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.5. Meter-counter, with alarm to predetermine the length of production runs
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.7. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 200 mm (8").
- Fabric roll diameter in exit 200 mm (8").
- Printing paper roll diameter in entry 150 mm (6") - Larger diameters on request.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL T02-1300

- Printing paper roll diameter in exit 150 mm (6") - Larger diameters on request.
- Protection paper roll diameter in entry 200 mm (8").
- Protection paper roll diameter in exit 200 mm (8").

6. TECHNICAL DATA:

6.1. Installed power: 7 kW

6.2. Average electric consumption: 5 kW/h

6.3. Compressed air pressure: 3 - 8 bar

6.4. Mechanic speed: 0.1 - 1.7 m/min

6.5. Overall dimensions (with front table): width 2.115 mm (83"). length 1.905 mm (75"). height 1.235 mm (49").

6.6. Net weight: 640 kg

6.7. Machine produced according to CE rules

6.8. Customs tariff: 84 51 80 30



Headquarter (India) : DCC Print Vision LLP,

802, Kamla Executive Park, Opp. Vazir Glass Work, Off. M.V. Road, J. B. Nagar,
Andheri (East), Mumbai- 400 059, India. Tel. : +91 022 4085 5000



+91 9930 200 400



marketing@groupdcc.com



www.groupdcc.com



OUR FOOTPRINTS : TIRUPPUR

+91 93630 21265

BANGLADESH

+88 01714220088

LUDHIANA

+91 98719 88775

KOLKATA

+91 98314 72212

BENGALURU

+91 95855 44265

DELHI

+91 98719 88775

SURAT

+91 86575 90290