



Efficient printing and unrivalled textile print quality, now with orange and violet inks.

SureColor SC-F6430

Epson new powerhouses, SureColor F6430/F6430H, are setting fresh benchmarks in textile printers with their reliable and superior print quality. Offering a high-performance solution for small to mid-sized textile production companies, these 44" digital dye sublimation printers are equipped with an integrated ink system and the all-new PrecisionCore MicroTFP Printhead. With the addition of orange and violet inks, the SC-F6430H raises the bar with its 6-colour printing, delivering fluorescent brightness and unique colours for specific printing needs.



ST Ink



IT'S IN THE DETAILS.





Reliable & High Productivity

Equipped with the all-new 1.33-inch PrecisionCore MicroTFP printhead, printing speeds are improved by approximately 20%'.

Integrated Ink System

Minimise downtime with the improved 1.6L ink capacity along with easy and user-friendly machine operation and maintenance. Ink life after installation has been improved up to one year from just 25 days.

Improved Colour Options

SureColor SC-F6430H

Expand business opportunities with SC-F6430H's improved colour set options which are fluorescent yellow and fluorescent pink, light cyan and light magenta, and orange and violet.

MODEL NUMBER	SC-F6430	SC-F6430H	PRINTER DIMENSION
PRINT			SC-F6430/F6430H
Technology 1	PrecisionCore Inkjet Technology		Without Take Up Reel
Technology 2	Variable-Sized Droplet Technology		Without take op neer
Printhead	PrecisionCore MicroTFP Print The number of nozzles:		
Nozzle Configuration	3.200 nozzles	The number of nozzles: 2,400 nozzles	100 E
	3,200 nozzies CMYHDK:	CMYHDKLcLm: 2,400 nozzles (400 x 6 colours)	1,128 mm
	3,200 nozzles	CMYHDKECETT. 2,400 nozzles (400 x 6 colours)	1,120
	(800 x 4 colours)	CMYHDKOrV: 2,400 nozzles (400 x 6 colours)	
Maximum Resolution	600 x 1,200 dpi		
Minimum Ink Droplet Volume	3.6pl		1,608 mm
Maximum Print Speed	78.3 m²/h	38.8 m²/h	1,008 11111
Margin (Roll Paper)		mm (Top) / 5~150 mm (Bottom)	
INK			With Take Up Reel
Ink Types	Dye Sublimation Transfer Ink		
Ink Brand Name	UltraChrome DS Ink	UltraChrome DS 6 Ink	1700 E
Colours	Cyan, Magenta, Yellow, High		1,128 mm
	N/A	Light Cyan, Light Magenta,	1,12811111
		Fluorescent Yellow, Fluorescent Pink,	120
		Orange, Violet	•
Ink Capacity	1.6L		916 mm
Ink Case	Ink Supply Unit		1,608 mm
MEDIA HANDLING	5 11 (6)		
Paper Path	Roll (Single Roll)		UltraChrome DS Inks
Paper Feed Method	Friction Feed		Cyan C13T53Q200
Paper Width (Roll)	254 mm to 1,118 mm (10" to 44")		Magenta C13T53Q300
Paper Thickness (Roll)	Up to 0.5 mm		Yellow C13T53Q400
CONTROL PANEL	4 3" Colour I CD Touch Panel		High Density Black C13T53Q900
Colour/Size CONNECTIVITY	4.3" Colour LCD Touch Panel		
	Super Speed USB, 100BASE-TX/1000BASE-T		UltraChrome DS 6 Inks
Interfaces Printer Language	ESC/P raster		Light Cyan C13T53Q500 Light Magenta C13T53Q600
Memory	1 GB		Fluorescent Pink C13T53Q800
	<u> </u>		Fluorescent Yellow C13T53Q700
ENVIRONMENT CHARACTERISTICS			Orange C13T53QA00
Temperature (°C)	Operating: 10 °C - 35 °C		Violet C13T53QD00
	Storage: -20 °C - 40 °C		Outions & Consumables
Humidity	Operating: 20 – 80% (No Condensation)		Options & Consumables Auto Take-up Reel Unit C12C934671
DIMENSIONS			Roll Adapter C12C934701
Printer (W x D x H)	With Take Up Reel: 1,608 x 916 mm x 1,128 mm		Maintenance Kit C13S210063
	Without Take Up Reel: 1,608 x 745 mm x 1,128 mm		Head Maintenance Kit C13S400145
WEIGHT			Waste Ink Bottle C13T724000
With Take Up Reel:	Approx. 133 kg	Approx. 140 kg	Auto Cutter Spare Blade C13S902006
Without Take Up Reel:	Approx. 120 kg	Approx. 127 kg	*Bundled for SC-F6430H.
ELECTRICAL SPECIFICATION	ON		
Voltage	AC 220 - 240V (withstand vo	ltage AC 400V)	
Frequency	50/60 Hz		
Power Consumption	Operating: Approx. 80W		©2022 Epson Singapore Pte Ltd. All Rights Reserved Reproduction in part or in whole, without the written
	Ready: Approx. 36W		permission from Epson, is strictly prohibited.
	Sleep: Approx. 19W		EPSON and EXCEED YOUR VISION are registered
	Power Off (Standby): Approx. 0.3W		trademarks of Seiko Epson Corporation.
ACOUSTIC NOISE LEVEL	50.5 (1)		All other product names and other company names used herein are for identification purposes only and
Sound Pressure Level - db(A)	53.5 db		are the trademarks or registered trademarks of their
Sound Power Level - B(A)	7.0 B		respective owners.
UTILITY SOFTWARE	Francisco Original Harborn Francisco Nat Britan Francisco Original Construction		Epson disclaims any and all rights in those marks. Projected images shown herein are simulations.
Bundled in CD	Epson Software Updater, Epson Net Print, Epson Net Config SE		The actual product design and contents may vary.
Web Delivery	Epson Edge Print Pro, Epson Edge Colour, Epson Device Admin		Specifications are subject to change without notice ar
CERTIFICATIONS	LISA and Canada (NIDT) Contified) FLL(Law Voltage Binestine)		may vary between countries. Please check with local Epson offices for more information.
Safety	USA and Canada (NRTL Certified), EU (Low Voltage Directive),		
	Custom Union (Russia, Belarus, Kazakhstan) (EAC), Morocco Likraino, India, Argentino (S. mark), Movico (NOM), LIK (LIKCA)		
	Morocco, Ukraine, India, Argentina (S-mark), Mexico (NOM), UK (UKCA),		Dealer's Stamp
WHAT'S IN THE BOX	Germany (GS), Singapore, Cambodia Main unit, Stand, Wasta ink battle, Ball adapter, Epson Edge Brint Bre DVD		
WHAT S IN THE BUX	Main unit, Stand, Waste ink bottle, Roll adapter, Epson Edge Print Pro DVD, Software CD, Paper manual and instructions, Warranty sheet, AC cable,		
		and instructions, warranty sheet, AC cable, e-up reel unit (standard bundle only for F6430H)	
	waintenance tools, Auto take		
			Information correct at time of printing.



Headquarter (India): DCC Print Vision LLP,

802, Kamla Executive Park, Opp. Vazir Glass Work, Off. M. V. Road, J. B. Nagar, Andheri (East), Mumbai- 400 059, India. Tel. : +91 022 4085 5000







